

**PERMABOIS FLOORING SPECIFICATIONS ( JULY 2026 )**

European White Oak Collections (3/4" - 19mm)							
FLOORING DIMENSIONS	3/4" X 5" X 127mm 18mm	3/4" X 5" X 127mm 18mm	3/4" X 5" X 127mm 18mm	3/4" X 5" X 127mm 18mm	3/4" X 7 1/2" X 190.5mm 18mm	3/4" X 7 1/2" X 190.5mm 18mm	3/4" X 10 1/4" X 260.4mm 19mm
GRADE AND CLASSIFICATION	SELECT & BETTER	EXCLUSIVE	SELECT & BETTER	SELECT & BETTER	SELECTION	TRADITION - CHARACTER GRADE	TRADITION - CHARACTER GRADE
STYLE AND FORMAT	HERRINGBONE FIXED LENGTH 5/8" - 625.5mm 24	PLANK	PLANK	CHEVRON FIXED LENGTH 24 5/8" - 625.5mm	WIDE PLANK	WIDE PLANK	EXTRA WIDE PLANK
PERMABOIS FINISH	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS
SURFACE APPEARANCE	SMOOTH	BRUSHED	SMOOTH	SMOOTH	SMOOTH	BRUSHED	WIREBRUSHED
BEVEL TYPE	MICRO BEVEL	MICRO BEVEL	MICRO BEVEL	MICRO BEVEL	MICRO BEVEL	MICRO BEVEL	MICRO BEVEL
CONSTRUCTION TYPE AND PROFILING	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 15mm T&G 4 SIDES	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 16mm T&G 4 SIDES	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 15mm T&G 4 SIDES	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 15mm T&G 4 SIDES	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 15mm T&G 4 SIDES	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 15mm T&G 4 SIDES	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 5/8" - 15mm T&G 4 SIDES
FLOORING WEAR LAYER	DRY-SAWN 1/8" - 3mm	DRY-SAWN 1/8" - 2mm	DRY-SAWN 1/8" - 3mm	DRY-SAWN 1/8" - 3mm	DRY-SAWN 1/8" - 3mm	DRY-SAWN 1/8" - 3mm	DRY-SAWN 5/32" - 4mm
NOTE : DIMENSIONS MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS							
INSTALLATION TECHNIQUES	NAILED - NAIL ASSISTED - GLUED FULL SPREAD	NAILED - NAIL ASSISTED - GLUED FULL SPREAD	NAILED - NAIL ASSISTED - GLUED FULL SPREAD	NAILED - NAIL ASSISTED - GLUED FULL SPREAD	NAIL ASSISTED - GLUED FULL SPREAD	NAIL ASSISTED - GLUED FULL SPREAD	GLUED FULL SPREAD
RADIANT HEAT TOLERANCE	YES THESE ENGINEERED PERMABOIS OILED FLOORS ARE WELL-SUITED FOR USE OVER HOT WATER OR ELECTRICAL RADIANT HEATED SUBFLOORS, MAINTAIN RELATIVE HUMIDITY BETWEEN 30%-60% AT ALL TIME, PLEASE FOLLOW MANUFACTURER AND INSTALLATION INSTRUCTIONS FOR APPLICABLE WARRANTIES						
GENERAL USAGE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE
LENGTHS / BOX	FIXED LENGTHS 23 5/8" - 600.1mm	RANDOM LENGTHS FROM 18" TO 85"	RANDOM LENGTHS FROM 18" TO 85" (457mm - 2160mm)	FIXED LENGTHS 24 5/8" - 625.5mm	RANDOM LENGTHS FROM 18" TO 75" (457mm - 1905mm)	RANDOM LENGTHS FROM 18" TO 75" (457mm - 1905mm)	RANDOM LENGTHS FROM 18" TO 87" (457mm - 2210mm)
QUANTITY / BOX	15.5 SF/BOX	20.5 SF/BOX	20.5 SF/BOX	16.82 SF/BOX	19.5 SF/BOX	19.5 SF/BOX	24.62 SF/BOX
NOTE : DIMENSIONS AND QUANTITIES MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS							
STRUCTURAL WARRANTY	WITH PROPER MAINTENANCE AND IN RESPECT WITH RELATIVE HUMIDITY ( MAINTAIN RH BETWEEN 35%-55% ) YOUR PERMABOIS OILED FLOORS SHOULD LAST MANY LIFETIMES.. WE HOWEVER NEED TO LIMIT STRUCTURAL WARRANTY AT 25 YEARS, This warranty extends only to the original end-user. Warranties are non-transferable with the exception of warranty transfer from contractor to owner.						
MAINTENANCE RESIDENTIAL	ONLY USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS.						
MAINTENANCE COMMERCIAL	USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS. THE OCCASIONAL USE OF PERMALUSTRE IS RECOMMENDED FOR HIGH TRAFFIC COMMERCIAL ENVIRONMENTS, RESPECT MANUFACTURERS GUIDELINES TO AVOID WAX BUILDUP, PLEASE FOLLOW INSTRUCTIONS.						
TECHNICAL REFERENCES	CARB COMPLIANT PHASE 2 ( Below 0.05 ppm. )						
	FORMALDEHYDE EMISSION (ASTM-E-1333-02) <0.01ppm (depending on species)						
SCSglobal	Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m3 (in compliance with CDPH/EHLB Standard Method v1.2-2017)						
FSC FORESTS FOR ALL FOREVER	Indoor Air quality Certified to SCS-EC10.3-2014 v4.1 Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017.						