



**PERMABOIS FLOORING SPECIFICATIONS ( JULY 2026 )**

<b>Hard Maple Collections</b>					
FLOORING DIMENSIONS	3/4" X 5" 18mm X 125mm	3/4" x 7 1/2" 18mm X 190.5mm			
GRADE AND CLASSIFICATION	SELECTION	TRADITION			
STYLE AND FORMAT	PLANK	WIDE PLANK			
PERMABOIS FINISH	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS			
SURFACE APPEARANCE	SMOOTH	DISTRESSED			
BEVEL TYPE	MICRO BEVEL	PRESSED BEVEL			
CONSTRUCTION TYPE AND PROFILING	MULTI-PLY CORE ENGINEERED 11/16" - 16mm T&G 4 SIDES	MULTI-PLY CORE ENGINEERED 11/16" - 16mm T&G 4 SIDES			
FLOORING WEAR LAYER	DRY-SAWN 5/64" - 2mm	DRY-SAWN 5/64" - 2mm			
	NOTE : DIMENSIONS MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS				
INSTALLATION TECHNIQUES	NAILED - NAIL ASSISTED - GLUED FULL SPREAD	NAIL ASSISTED - GLUED FULL SPREAD			
RADIANT HEAT TOLERANCE	YES THESE ENGINEERED PERMABOIS OILED FLOORS ARE WELL-SUITED FOR USE OVER HOT WATER OR ELECTRICAL RADIANT HEATED SUBFLOORS, MAINTAIN RELATIVE HUMIDITY BETWEEN 30%-60% AT ALL TIME, PLEASE FOLLOW MANUFACTURER AND INSTALLATION INSTRUCTIONS FOR APPLICABLE WARRANTIES				
GENERAL USAGE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE			
LENGTHS / BOX	RANDOM LENGHT FROM 18" TO 75" (457mm 1905mm)	RANDOM LENGHT FROM 18" TO 75" (457mm 1905mm)			
QUANTITY / BOX	18.65 SF/BOX	19.5 SF/BOX			
	NOTE : DIMENSIONS AND QUANTITIES MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS				
STRUCTURAL WARRANTY	WITH PROPER MAINTENANCE AND IN RESPECT WITH RELATIVE HUMIDITY ( MAINTAIN RH BETWEEN 35%-55% ) YOUR PERMABOIS OILED FLOORS SHOULD LAST MANY LIFETIMES.. WE HOWEVER NEED TO LIMIT STRUCTURAL WARRANTY AT 25 YEARS, This warranty extends only to the original end-user. Warranties are non-transferable with the exception of warranty transfer from contractor to owner.				
MAINTENANCE RESIDENTIAL	ONLY USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS'S OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS.				
MAINTENANCE COMMERCIAL	USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS'S OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS. THE OCCASIONAL USE OF PERMALUSTRE IS RECOMMENDED FOR HIGH TRAFFIC COMMERCIAL ENVIRONMENTS, RESPECT MANUFACTURERS GUIDELINES TO AVOID WAX BUILDUP, PLEASE FOLLOW INSTRUCTIONS.				
TECHNICAL REFERENCES	CARB COMPLIANT PHASE 2 ( Below 0.05 ppm. )				
	FORMALDEHYDE EMISSION (ASTM-E-1333-02) <0.01ppm (depending on species)				
	Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m3 (in compliance with CDPH/EHLB Standard Method v1.2-2017)				
	Indoor Air quality Certified to SCS-EC10.3-2014 v4.1 Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017.				