

PERMABOIS FLOORING SPECIFICATIONS

European White Oak Collections (9/16" - 14mm)

FLOORING DIMENSIONS	9/16" X 7 1/2" X 190.5mm	14mm				
GRADE AND CLASSIFICATION	TRADITION - CHARACTER GRADE					
STYLE AND FORMAT	WIDE PLANK					
PERMABOIS FINISH	SATURATED AIR DRIED NATURAL VEGETABLE OILS					
SURFACE APPEARANCE	WIREBRUSHED					
BEVEL TYPE	MICRO BEVEL					
CONSTRUCTION TYPE AND PROFILING	3-PLY CORE ENGINEERED 7/16" - 11mm T&G 4 SIDES					
FLOORING WEAR LAYER	DRY-SAWN 1/8" - 3mm					
NOTE : DIMENSIONS MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS						
INSTALLATION TECHNIQUES	GLUED FULL SPREAD					
RADIANT HEAT TOLERANCE	YES THESE ENGINEERED PERMABOIS OILED FLOORS ARE WELL-SUITED FOR USE OVER HOT WATER OR ELECTRICAL RADIANT HEATED SUBFLOORS, MAINTAIN RELATIVE HUMIDITY BETWEEN 30%-60% AT ALL TIME, PLEASE FOLLOW MANUFACTURER AND INSTALLATION INSTRUCTIONS FOR APPLICABLE WARRANTIES					
GENERAL USAGE	INTERIOR FLOORS ABOVE OR BELOW GRADE					
LENGHTS / BOX	RANDOM LENGTH FROM 18" TO 75" (457mm 1905mm)					
QUANTITY / BOX	27.25 SF/BOX					
NOTE : DIMENSIONS AND QUANTITIES MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS						
STRUCTURAL WARRANTY	WITH PROPER MAINTENANCE AND IN RESPECT WITH RELATIVE HUMIDITY (MAINTAIN RH BETWEEN 35%-55%) YOUR PERMABOIS OILED FLOORS SHOULD LAST MANY LIFETIMES.. WE HOWEVER NEED TO LIMIT STRUCTURAL WARRANTY AT 25 YEARS, This warranty extends only to the original end-user. Warranties are non-transferable with the exception of warranty transfer from contractor to owner.					
MAINTENANCE RESIDENTIAL	ONLY USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS'S OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS.					
MAINTENANCE COMMERCIAL	USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS'S OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS. THE OCCASIONAL USE OF PERMALUSTRE IS RECOMMENDED FOR HIGH TRAFFIC COMMERCIAL ENVIRONMENTS, RESPECT MANUFACTURERS GUIDELINES TO AVOID WAX BUILDUP, PLEASE FOLLOW INSTRUCTIONS.					
TECHNICAL REFERENCES	CARB COMPLIANT PHASE 2 (Below 0.05 ppm.)					
	FORMALDEHYDE EMISSION (ASTM-E-1333-02) <0.01ppm (depending on species)					
	FORMALDEHYDE EMISSION (EN 120-92) CLASS E1					
	VOC TOTAL (ASTM-D-6670-01) <0.011ppm (depending on species)					