

PERMABOIS FLOORING SPECIFICATIONS (AUGUST 2022)

European White Oak Collections (3/4" - 19mm)

FLOORING DIMENSIONS	3/4" X 5" 19mm X 127mm	3/4" X 5" 19mm X 127mm	3/4" X 5" X 127mm	19mm	3/4" X 7 1/2" X 190.5mm	19mm	3/4" X 7 1/2" X 190.5mm	19mm	3/4" X 7 1/2" X 190.5mm	19mm	3/4" X 10 1/4" X 260.4mm	19mm
GRADE AND CLASSIFICATION	SELECT & BETTER	SELECT & BETTER	SELECT & BETTER		SELECT & BETTER		SELECTION		TRADITION - CHARACTER GRADE		TRADITION - CHARACTER GRADE	
STYLE AND FORMAT	HERRINGBONE FIXED LENGTH 24 5/8" - 625.5mm	PLANK	CHEVRON FIXED LENGTH 5/8" - 625.5mm	24	WIDE PLANK		WIDE PLANK		WIDE PLANK		EXTRA WIDE PLANK	
PERMABOIS FINISH	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS		SATURATED AIR DRIED NATURAL VEGETABLE OILS		SATURATED AIR DRIED NATURAL VEGETABLE OILS		SATURATED AIR DRIED NATURAL VEGETABLE OILS		SATURATED AIR DRIED NATURAL VEGETABLE OILS	
SURFACE APPEARANCE	SMOOTH	SMOOTH	SMOOTH		SMOOTH		SMOOTH		BRUSHED		WIREBRUSHED	
BEVEL TYPE	MICRO BEVEL	MICRO BEVEL	MICRO BEVEL		MICRO BEVEL		MICRO BEVEL		MICRO BEVEL		MICRO BEVEL	
CONSTRUCTION TYPE AND PROFILING	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 16mm T&G 4 SIDES	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 16mm T&G 4 SIDES	ENGINEERED MULTI-PLY BALTIC BIRCH CORE 11/16" - 16mm T&G 4 SIDES		ENGINEERED 3-PLY EUROPEAN PINE CORE 5/8" - 15mm T&G 4 SIDES		ENGINEERED 3-PLY EUROPEAN PINE CORE 11/16" - 16mm T&G 4 SIDES		ENGINEERED 3-PLY EUROPEAN PINE CORE 11/16" - 16mm T&G 4 SIDES		ENGINEERED MULTI-PLY BALTIC BIRCH CORE 5/8" - 15mm T&G 4 SIDES	
FLOORING WEAR LAYER	DRY-SAWN 1/8" - 3mm	DRY-SAWN 1/8" - 3mm	DRY-SAWN 1/8" - 3mm	1/8"	DRY-SAWN 5/32" - 4mm		DRY-SAWN 1/8" - 3mm	1/8"	DRY-SAWN 1/8" - 3mm	1/8"	DRY-SAWN 5/32" - 4mm	5/32"
	NOTE : DIMENSIONS MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS											
INSTALLATION TECHNIQUES	NAILED - NAIL ASSISTED - GLUED FULL SPREAD	NAILED - NAIL ASSISTED - GLUED FULL SPREAD	NAILED - ASSISTED - SPREAD	NAIL GLUED FULL	NAIL ASSISTED - FULL SPREAD		NAIL ASSISTED - FULL SPREAD	GLUED	NAIL ASSISTED - FULL SPREAD	GLUED	GLUED FULL SPREAD	
RADIANT HEAT TOLERANCE	YES THESE ENGINEERED PERMABOIS OILED FLOORS ARE WELL-SUITED FOR USE OVER HOT WATER OR ELECTRICAL RADIANT HEATED SUBFLOORS, MAINTAIN RELATIVE HUMIDITY BETWEEN 30%-60% AT ALL TIME, PLEASE FOLLOW MANUFACTURER AND INSTALLATION INSTRUCTIONS FOR APPLICABLE WARRANTIES											
GENERAL USAGE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE		INTERIOR FLOORS ABOVE OR BELOW GRADE		INTERIOR FLOORS ABOVE OR BELOW GRADE		INTERIOR FLOORS ABOVE OR BELOW GRADE		INTERIOR FLOORS ABOVE OR BELOW GRADE	
LENGTHS / BOX	FIXED LENGHTS 23 5/8" - 600.1mm	RANDOM LENGHTS FROM 18" TO 85" (457mm - 2160mm)	FIXED LENGHTS 5/8" - 625.5mm	24	RANDOM LENGHTS FROM 18" TO 85" (457mm - 2160mm)		RANDOM LENGHTS FROM 18" TO 75" (457mm - 1905mm)		RANDOM LENGHTS FROM 18" TO 75" (457mm - 1905mm)		RANDOM LENGHTS FROM 18" TO 87" (457mm - 2210mm)	
QUANTITY / BOX	15.5 SF/BOX	20.5 SF/BOX	16.82 SF/BOX		22.5 SF/BOX		19.5 SF/BOX		19.5 SF/BOX		24.62 SF/BOX	
	NOTE : DIMENSIONS AND QUANTITIES MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS											
STRUCTURAL WARRANTY	WITH PROPER MAINTENANCE AND IN RESPECT WITH RELATIVE HUMIDITY (MAINTAIN RH BETWEEN 35%-55%) YOUR PERMABOIS OILED FLOORS SHOULD LAST MANY LIFETIMES.. WE HOWEVER NEED TO LIMIT STRUCTURAL WARRANTY AT 25 YEARS, This warranty extends only to the original end-user. Warranties are non-transferable with the exception of warranty transfer from contractor to owner.											
MAINTENANCE RESIDENTIAL	ONLY USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS.											
MAINTENANCE COMMERCIAL	USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS. THE OCCASIONAL USE OF PERMALUSTRE IS RECOMMENDED FOR HIGH TRAFFIC COMMERCIAL ENVIRONMENTS, RESPECT MANUFACTURERS GUIDELINES TO AVOID WAX BUILDUP, PLEASE FOLLOW INSTRUCTIONS.											
TECHNICAL REFERENCES	CARB COMPLIANT PHASE 2 (Below 0.05 ppm.)											
	FORMALDEHYDE EMISSION (ASTM-E-1333-02) <0.01ppm (depending on species)											
	FORMALDEHYDE EMISSION (EN 120-92) CLASS E1											
	VOC TOTAL (ASTM-D-6670-01) <0.011ppm (depending on species)											