

PERMABOIS FLOORING SPECIFICATIONS (AUGUST 2022)

Hard Maple Collections					
FLOORING DIMENSIONS	3/4" X 6" X 152mm	19mm	3/4" x 7 1/2" X 190.5mm	19mm	
GRADE AND CLASSIFICATION	SELECTION		TRADITION		
STYLE AND FORMAT	PLANK		WIDE PLANK		
PERMABOIS FINISH	SATURATED AIR DRIED NATURAL VEGETABLE OILS		SATURATED AIR DRIED NATURAL VEGETABLE OILS		
SURFACE APPEARANCE	SMOOTH		DISTRESSED		
BEVEL TYPE	MICRO BEVEL		PRESSED BEVEL		
CONSTRUCTION TYPE AND PROFILING	MULTI-PLY CORE ENGINEERED 11/16" - 17mm T&G 4 SIDES		MULTI-PLY CORE ENGINEERED 11/16" - 17mm T&G 4 SIDES		
FLOORING WEAR LAYER	DRY-SAWN 5/64" - 2mm		DRY-SAWN 5/64" - 2mm		
NOTE : DIMENSIONS MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS					
INSTALLATION TECHNIQUES	NAILED - ASSISTED - SPREAD	NAIL GLUED FULL SPREAD	NAIL ASSISTED - FULL SPREAD	GLUED	
RADIANT HEAT TOLERANCE	YES THESE ENGINEERED PERMABOIS OILED FLOORS ARE WELL-SUITED FOR USE OVER HOT WATER OR ELECTRICAL RADIANT HEATED SUBFLOORS, MAINTAIN RELATIVE HUMIDITY BETWEEN 30%-60% AT ALL TIME, PLEASE FOLLOW MANUFACTURER AND INSTALLATION INSTRUCTIONS FOR APPLICABLE WARRANTIES				
GENERAL USAGE	INTERIOR FLOORS ABOVE OR BELOW GRADE		INTERIOR FLOORS ABOVE OR BELOW GRADE		
LENGTHS / BOX	RANDOM LENGHT FROM 18" TO 75" (457mm 1905mm)	FROM	RANDOM LENGHT FROM 18" TO 75" (457mm 1905mm)		
QUANTITY / BOX	18.65 SF/BOX		19.5 SF/BOX		
NOTE : DIMENSIONS AND QUANTITIES MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS					
STRUCTURAL WARRANTY	WITH PROPER MAINTENANCE AND IN RESPECT WITH RELATIVE HUMIDITY (MAINTAIN RH BETWEEN 35%-55%) YOUR PERMABOIS OILED FLOORS SHOULD LAST MANY LIFETIMES.. WE HOWEVER NEED TO LIMIT STRUCTURAL WARRANTY AT 25 YEARS, This warranty extends only to the original end-user. Warranties are non-transferable with the exception of warranty transfer from contractor to owner.				
MAINTENANCE RESIDENTIAL	ONLY USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS'S OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS.				
MAINTENANCE COMMERCIAL	USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS'S OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS. THE OCCASIONAL USE OF PERMALUSTRE IS RECOMMENDED FOR HIGH TRAFFIC COMMERCIAL ENVIRONMENTS, RESPECT MANUFACTURERS GUIDELINES TO AVOID WAX BUILDUP. PLEASE FOLLOW INSTRUCTIONS.				
TECHNICAL REFERENCES	CARB COMPLIANT PHASE 2 (Below 0.05 ppm.)				
	FORMALDEHYDE EMISSION (ASTM-E-1333-02) <0.01ppm (depending on species)				
	FORMALDEHYDE EMISSION (EN 120-92) CLASS E1				
	VOC TOTAL (ASTM-D-6670-01) <0.011ppm (depending on species)				