

PERMABOIS FLOORING SPECIFICATIONS (AUGUST 2022)

Hickory Collections

FLOORING DIMENSIONS	9/16" X 7 1/2" X 190.5mm 14mm	3/4" X 6" X 152mm 19mm	3/4" X 7 1/2" X 190.5mm 19mm			
GRADE AND CLASSIFICATION	TRADITION	SELECTION	TRADITION			
STYLE AND FORMAT	WIDE PLANK	PLANK	WIDE PLANK			
PERMABOIS FINISH	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS	SATURATED AIR DRIED NATURAL VEGETABLE OILS			
SURFACE APPEARANCE	HAND SCRAPPED	SMOOTH	DISTRESSED			
BEVEL TYPE	PRESSED BEVEL	MICRO BEVEL	PRESSED BEVEL			
CONSTRUCTION TYPE AND PROFILING	MULTI-PLY CORE ENGINEERED 7/16" - 11mm T&G 4 SIDES	MULTI-PLY CORE ENGINEERED 11/16" - 16mm T&G 4 SIDES	MULTI-PLY CORE ENGINEERED 11/16" - 16mm T&G 4 SIDES			
FLOORING WEAR LAYER	DRY-SAWN - 3mm 1/8"	DRY-SAWN - 2mm 5/64"	DRY-SAWN 5/64" - 2mm			
NOTE : DIMENSIONS MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS						
INSTALLATION TECHNIQUES	NAIL ASSISTED - GLUED FULL SPREAD	NAILED - ASSISTED - SPREAD	NAIL ASSISTED - GLUED FULL SPREAD			
RADIANT HEAT TOLERANCE	NO, THESE ENGINEERED PERMABOIS OILED FLOORS ARE NOT SUITED FOR USE OVER HOT WATER OR ELECTRICAL RADIANT HEATED SUBFLOORS, STILL MAINTAIN RELATIVE HUMIDITY BETWEEN 35%-55%.					
GENERAL USAGE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE	INTERIOR FLOORS ABOVE OR BELOW GRADE			
LENGTHS / BOX	RANDOM LENGHT FROM 18" TO 75" (457mm 1905mm)	RANDOM LENGHT FROM 18" TO 75" (457mm 1905mm)	RANDOM LENGHT FROM 18" TO 75" (457mm 1905mm)			
QUANTITY / BOX	27.25 SF/BOX	18.65 SF/BOX	19.5 SF/BOX			
NOTE : DIMENSIONS AND QUANTITIES MAY VARY SLIGHTLY DUE TO PRODUCTION REQUIREMENTS						
STRUCTURAL WARRANTY	WITH PROPER MAINTENANCE AND IN RESPECT WITH RELATIVE HUMIDITY (MAINTAIN RH BETWEEN 35%-55%) YOUR PERMABOIS OILED FLOORS SHOULD LAST MANY LIFETIMES.. WE HOWEVER NEED TO LIMIT STRUCTURAL WARRANTY AT 25 YEARS. (Warranties are non-transferable with the exception of warranty transfer from contractor to owner)					
MAINTENANCE RESIDENTIAL	ONLY USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS'S OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS.					
MAINTENANCE COMMERCIAL	ONLY USE PERMACLEAN WOOD SOAP FOR MAINTENANCE OF PERMABOIS'S OILED WOOD FLOORS, IT CLEANS AND NOURISHES YOUR FLOORS ALL IN ONE EASY STEP. SOYBEAN AND COCONUT OILS BASED CONCENTRATES TO BE DILUTED IN WARM WATER, PLEASE FOLLOW INSTRUCTIONS. THE OCCASIONAL USE OF PERMALUSTRE IS RECOMMENDED FOR HIGH TRAFFIC COMMERCIAL ENVIRONMENTS, RESPECT MANUFACTURERS GUIDELINES TO AVOID WAX BUILDUP. PLEASE FOLLOW INSTRUCTIONS.					
TECHNICAL REFERENCES	CARB COMPLIANT PHASE 2 (Below 0.05 ppm.)					
	FORMALDEHYDE EMISSION (ASTM-E-1333-02) <0.01ppm (depending on species)					
	FORMALDEHYDE EMISSION (EN 120-92) CLASS E1					
	VOC TOTAL (ASTM-D-6670-01) <0.011ppm (depending on species)					